



CHEMILUBE
Speciality Lubricants

ELITE INDUSTRIES

12, Samkit, Sagar Signature, Waliv - Phata, Sativali,
Vasai (East), Dist. Thane Tel. : 0250 - 3248281
E-mail : elite_ent@hotmail.com • Website : www.chemilube.co.in

CHEMILUBE DRY COAT - 1500

DESCRIPTION :- DRY CORROSION INHIBITOR

BENEFITS

- :-
- Firm coating which does not crack or peel.
 - Acts as anti-corrosion agent.
 - Fast air drying and flexible film.
 - Water, heat grease, oil, dust and acid resistant.
 - Does not contain CTC or CFC hence environment friendly.
 - Conforms to RoHS norms.

APPLICATIONS :-

- Dies, terminals, motor windings, cables, spare parts, out door equipment, machined parts, electrical connection coils.

CHARACTERISTICS:-

TESTS	SPECIFICATIONS
Colour	Colourless / Red
Odour	Mild
Density	0.90+/- 0.05
Coating	Dry
Curing Time	Max. 30 min.
Coating Thickness	10-15 microns
Anti Corrosive Property	Passes
Propellant	Non CFC
Shelf Life	24 Months

PACKING SIZE: 500 M.L. AEROSOL PACK

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

**T
E
C
H
N
I
C
A
L

D
A
T
A

S
H
E
E
T**